

FIND IT! WITH



SENSIT[®] RLD-2

REFRIGERANT GAS LEAK DETECTOR



VERSATILE

Automatically detects all existing refrigerants and blends, including 404A.

EASY TO USE

High and low sensitivity settings and one hand operation makes leak detection quick and easy.

NO ADJUSTMENTS

Detects all existing refrigerant with no adjustments necessary to select and detect different refrigerants.

FIND IT! WITH SENSIT[®] RLD-2 REFRIGERANT GAS LEAK DETECTOR



SPECIFICATIONS

PHYSICAL

Size: 3.5" x 10" X 1.6"
 Weight: 1.3 lb.
 Construction: High impact ABS
 Battery Power: 3 "C" alkaline batteries
 Battery Life: 8 hrs continuous operation
 Gooseneck: 16"
 Alarms: Audible and flashing LED

SENSOR

Type: Solid State
 Sensitivity: Low (normal) 0.5 oz./yr. R22
 High (scan) 0.3oz./yr. R22
 Response Time: Less than 1 second

Industry Applications

Air Conditioning Systems
 Heat Pumps
 Commercial Refrigeration Systems/Lines
 Refrigerator and Freezer Coils

FEATURES

Long battery life
 Long sensor life
 Adjustable tick rate system
 SENSIT[®] quality and durability

Partial List of Gases Sensed

CFS's, HCFC's, HFC's, SF6, Ethylene Oxide, R-11, R-12, R-22, R-113, R-114, R-123, R-125, R-134a, R-500, R-502

FOR MORE INFORMATION

J And N Enterprises, Inc.

851 Transport Drive
 Valparaiso, IN 46383-8432

Phone: (888) 4SENSIT

(473-6748)

(219) 465-2700

Fax: (219) 465-2701

www.gasleaksensors.com



Distributed by _____